

# Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

Xerox® VersaLink® C7000 Series Color Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to [www.connectkey.com](http://www.connectkey.com).

Convenience  
Stapler (includes  
Work Surface)



Office Finisher LX or Office  
Finisher (not shown) with  
optional Booklet Maker



High Capacity  
Feeder



Integrated Office Finisher Type A or  
Integrated Office Finisher (not pictured)



Single Tray Module



Single Tray  
with Stand



Three Tray  
Module



High-Capacity  
Tandem Tray

SYSTEM SPECIFICATIONS	VERSALINK® C7020	VERSALINK® C7025	VERSALINK® C7030
<b>One-sided Speed<sup>1</sup></b> 8.5 x 11 in./A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm	Up to 20 ppm (pages per minute) long edge feed (LEF) Up to 16 ppm Up to 11 ppm	Up to 25 ppm LEF Up to 19 ppm Up to 14 ppm	Up to 30 ppm LEF Up to 23 ppm Up to 17 ppm
<b>Two-sided Speed<sup>1</sup></b> 8.5 x 11 in./A4/210 x 297 mm 8.5 x 14 in./216 x 356 mm 11 x 17 in./A3/297 x 420 mm	Up to 16 ppm LEF Up to 9 ppm Up to 8 ppm	Up to 19 ppm LEF Up to 10 ppm Up to 9 ppm	Up to 23 ppm LEF Up to 12 ppm Up to 11 ppm
<b>Monthly Duty Cycle<sup>2</sup></b>	Up to 87,000 pages/month <sup>2</sup>	Up to 107,000 pages/month <sup>2</sup>	Up to 129,000 pages/month <sup>2</sup>
<b>Recommended Average Monthly Print Volume<sup>3</sup></b>	Up to 5,500 pages	Up to 6,250 pages	Up to 7,000 pages
<b>Hard Drive</b>	320 GB HDD (Optional on Desktop\Base Unit)		
<b>Processor</b>	1.05 GHz Dual-Core		
<b>Memory</b>	4 GB		

# Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

<b>Connectivity</b>	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported), NFC Tap-to-Pair			
<b>Controller Features</b>	Unified Address Book, Configuration Cloning, Scan Preview, Xerox Extensible Interface Platform®, Xerox App Gallery, Xerox® Standard Accounting, Network Accounting Enabled, Role Based Permissions, Convenience Authentication Enabled, Online Support			
<b>User Interface Languages</b>	English, French, Italian, German, Spanish, Brazilian Portuguese, Russian, Dutch, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Polish, Czech, Hungarian, Romanian, Catalan, Ukrainian, Croatian			
<b>DEVICE SPECIFICATIONS</b>	<b>VERSALINK® C7020</b>	<b>VERSALINK® C7025</b>	<b>VERSALINK® C7030</b>	
<b>ELECTRICAL REQUIREMENTS</b>				
<b>North America</b>	Voltage: 110-127 V -10%/+6% Frequency: 50/60 Hz +/-3%, 12A			
<b>Europe and Other Geographies</b>	Voltage: 220-240 V +/- 10% Frequency: 50 Hz +/-3%, 8A			
<b>POWER CONSUMPTION</b>				
<b>Printing<sup>4</sup></b>	For 110 V: 20 ppm = 0.9 kWh; 25 ppm = 1.1 kWh; 30 ppm = 1.5 kWh			
<b>Standby Mode<sup>4</sup></b>	80 Watts or less	80 Watts or less	94 Watts or less	
<b>Sleep Mode<sup>4</sup></b>	0.72 Watts or less			
<b>OPERATING ENVIRONMENT</b>				
<b>Required Temperature Range (Storage)</b>	32° to 95° F (0° to 35° C)			
<b>Required Temperature Range (Operating)</b>	50 to 90° F (10 to 32° C)			
<b>Required Relative Humidity</b>	10% to 85%			
<b>Sound Power Levels</b>	Printing: 6.70 B(A) or less • 20 ppm = 6.45 B(A); 25 ppm = 6.50 B(A); 30 ppm = 6.70 B(A) Standby: 4.10 B(A) or less • 20 ppm = 4.10 B(A); 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A) <b>Full System (including Finisher and HCF)</b> Printing: 20 ppm = 7.07 B(A); 25 ppm = 7.22 B(A); 30 ppm = 7.37 B(A) Standby: 20 ppm = 4.10 B(A); 25 ppm = 4.10 B(A); 30 ppm = 4.10 B(A)			
<b>Sound Pressure Levels</b>	Printing: 52.0 dB(A) • 20 ppm = 49.5 dB(A); 25 ppm = 50.0 dB(A); 30 ppm = 52.0 dB(A) Standby: 26.0 dB(A) • 20 ppm = 26.0 dB(A); 25 ppm = 26.0 dB(A); 30 ppm = 26.0 dB(A) <b>Full System (including Finisher and HCF)</b> Printing: 20 ppm = 55.5 dB(A); 25 ppm = 57.0 dB(A); 30 ppm = 58.5 dB(A) Standby: 20 ppm = 26.0 dB(A); 25 ppm = 26.0 dB(A); 30 ppm = 26.0 dB(A)			
<b>Boot Time (from Off to UI Ready)</b>	As fast as 98 seconds			
<b>Warm-up Time (from Sleep to UI Ready)</b>	As fast as 12 seconds			
<b>DIMENSIONS AND WEIGHT (UNPACKAGED)</b>	<b>WIDTH</b>	<b>DEPTH</b>	<b>HEIGHT</b>	<b>WEIGHT</b>
<b>Base Unit</b>	23.23 in./590 mm	26.41 in./670.8 mm	30.23 in./767.9 mm	147.71 lbs./67.0 kg
<b>Base Unit with Single Tray with Stand Module</b>	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./1118.6 mm	202.83 lbs./92.0 kg
<b>Base Unit with High Capacity Tandem Tray Module</b>	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./1118.6 mm	203.71 lbs./92.4 kg
<b>Base Unit with Three Tray Module</b>	24.24 in./615.7 mm	26.41 in./670.8 mm	44.04 in./ 1118.6 mm	208.34 lbs./94.5 kg

# Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

<b>Base Unit with Three Tray Module and Office Finisher LX (with Booklet Maker)</b>	47.0 in./1194.0 mm	26.8 in./681.8 mm	44.04 in./1118.6 mm	291.89 lbs./132.4 kg
<b>Base Unit with Three Tray Module and Office Finisher (with Booklet Maker)</b>	45.22 in./1148.6 mm	26.7 in./678.6 mm	44.04 in./1118.6 mm	273.81 lbs./124.2 kg

## CERTIFICATIONS

To view the latest list of certifications, go to [www.xerox.com/OfficeCertifications](http://www.xerox.com/OfficeCertifications).

PRINT	VERSALINK® C7020	VERSALINK® C7025	VERSALINK® C7030
<b>First-Print-Out Time</b>	As fast as 9.4 seconds color	As fast as 9.4 seconds color	As fast as 7.3 seconds color
	As fast as 7.2 seconds black	As fast as 7.1 seconds black	As fast as 5.6 seconds black
<b>Print Resolution</b>	Up to 1200 x 2400 dpi		
<b>Page Description Languages</b>	PCL® 5e, 6 PDF XPS TIFF JPEG HP-GL Adobe® PostScript® 3™ (Optional)		
<b>Maximum Print Area</b>	4 mm from Lead edge of paper, 2 mm from Side and Trail edges of paper		
<b>Print Features</b>	<ul style="list-style-type: none"> <li>Application Defaults</li> <li>Banner Pages Enable/Disable</li> <li>Bi-directional Real-time Status</li> <li>Booklet Layout</li> <li>Color Correction</li> <li>Color Adjustments (lightness, contrast, saturation, color balance)</li> <li>Draft Mode</li> <li>Finishing (requires finishing)</li> <li>Fit to New Paper Size</li> <li>Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages)</li> <li>Job Monitoring (Client or Local User Interface)</li> <li>LAN Fax (requires Fax Kit)</li> <li>N-up Page Layout (up to 16 pages per sheet)</li> <li>Paper Selection by Attribute</li> <li>Personal Print</li> <li>Print Around Enable/Disable</li> <li>Print from USB</li> <li>Sample Set</li> <li>Saved Job</li> <li>Scaling</li> <li>Secure Print</li> <li>Skip Blank Pages</li> <li>Special Pages (exception page programming: covers, inserts, exceptions pages)</li> <li>Store and Recall Driver Settings</li> <li>Stored Jobs Deletion</li> <li>Two-sided Printing (as default)</li> <li>Watermark (predefined and custom)</li> <li>Xerox® Earth Smart Driver Settings</li> </ul>		
<b>Print from USB</b>	<ul style="list-style-type: none"> <li>Allows walk-up printing from Type A USB port</li> <li>Supports direct printing from computer via Type B USB port</li> <li>Supported file formats: PDF, JPEG, TIFF, XPS, PDF/A</li> </ul>		

# Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

<b>Operating Systems</b>	Windows® 7, 8, 8.1, 10 Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016 Mac OS® version 10.12, 10.13 Citrix® Redhat® Enterprise Linux® Fedora Core IBM® AIX® HP-UX® Oracle® Solaris SUSE® SAP® Note: For information about supported versions for the above operating systems, please visit our Drivers & Downloads page and specify your device at <a href="http://www.support.xerox.com">www.support.xerox.com</a> .		
<b>Fonts</b>	PostScript fonts: 136 PCL fonts: 83		
<b>Xerox® Mobile Express Driver®</b>	Makes it easy for mobile users to find, use and manage Xerox® and non-Xerox® devices in every new location. Plug into a new network, and Mobile Express Driver® automatically discovers available printers and provides status and capability information. Save a list of “favorite” printers for each location, store application print settings for use on any printer in any network, and greatly reduce mobile support calls to IT.		
<b>Xerox® Global Print Driver®</b>	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox® devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls, and simplifying print services management.		
<b>Xerox® Pull Print Driver</b>	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.		
<b>COPY</b>	<b>VERSALINK® C7020</b>	<b>VERSALINK® C7025</b>	<b>VERSALINK® C7030</b>
<b>Document Scanner</b>	110-sheet Duplex Automatic Document Feeder (DADF)		
<b>Document Scanner Size</b>	Platen: Up to 13.1 x 17.2 in./332.0 x 437 mm DADF: Up to 11.7 x 17 in./297 x 431.8 mm		
<b>Simplex Copy Speed</b>	Up to 20 cpm (copies per minute) 8.5 x 11 in. Up to 20 cpm A4 (210 x 297 mm)	Up to 25 cpm (copies per minute) 8.5 x 11 in. Up to 25 cpm A4 (210 x 297 mm)	Up to 30 cpm (copies per minute) 8.5 x 11 in. Up to 30 cpm A4 (210 x 297 mm)
<b>Duplex Copy Speed</b>	Up to 17 cpm (copies per minute) 8.5 x 11 in. Up to 17 cpm A4 (210 x 297 mm)	Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)	Up to 18 cpm (copies per minute) 8.5 x 11 in. Up to 18 cpm A4 (210 x 297 mm)
<b>First-Copy-Out Time</b>	As fast as 9.0 seconds color As fast as 6.9 seconds black	As fast as 9.0 seconds color As fast as 6.9 seconds black	As fast as 7.2 seconds color As fast as 5.8 seconds black
<b>Sides (input: output)</b>	1:1, 1:2, 2:2 and 2:1		
<b>Quantity</b>	1 to 999		
<b>Resolution (max.)</b>	Up to 600 x 600 dpi		
<b>Reduction/Enlargement</b>	Variable zoom from 25% to 400% in 1% increments		
<b>Concurrency</b>	Concurrent scanning and printing		

<b>Copy Features</b>	Annotation (Page Numbers, Comments, Date Stamp, Bates Stamping)* Auto-color Sensing Automatic Background Suppression Book Copying with Center Erase Booklet Copying* Collation Color Balance Color Effects Darkness Control Edge Erase Front Cover ID Card Copy Image Enhancement Image Shift Lighten/Darken N-up Original Orientation Original Size Original Type Page Layout Reduce/Enlarge 25% to 400% Sample Copy Saturation Sharpness *Requires HDD/Productivity Kit
<b>SCAN</b>	
<b>Capability</b>	Black-and-white and color scanning
<b>Concurrency</b>	Scan while the system is printing copy or network print jobs, or while it is transferring scan to network or fax jobs
<b>Simplex Input Speed</b>	Black-and-white: Scan up to 55 ipm – 8.5 x 11 in./A4 (210 x 297 mm) Color: Scan up to 55 ipm – 8.5 x 11 in./55 ipm A4 (210 x 297 mm)
<b>Duplex Input Speed</b>	Black-and-white: Scan up to 26 ipm – 8.5 x 11 in./A4 (210 x 297 mm) Color: Scan up to 26 ipm – 8.5 x 11 in./26 ipm A4 (210 x 297 mm)
<b>Resolution</b>	Optical – 600 x 600 dpi
<b>Bit Depth</b>	24-bit color/8-bit grayscale
<b>Maximum Scan Area</b>	Platen: Up to 13.1 x 17.2 in./332 x 437 mm Document Feeder: 11.7 x 17 in./297 x 431.8 mm
<b>Network Filing Protocols</b>	FTP SMTP SMB
<b>File Formats</b>	JPG TIFF (single and multi-page) XPS (single and multi-page) PDF (single and multi-page) Searchable PDF via Optical Character Recognition (OCR) Password-protected PDF Linearized PDF (set via embedded web server) and PDF/A
<b>Scan Driver Compatibility (Network Only)</b>	WIA TWAIN

<b>Supported Scan Destinations</b>	Scan to Home Scan to USB Scan to Email Scan to Network (Browse FTP or Browse SMB)
<b>NETWORK SCANNING – SOFTWARE SOLUTIONS</b>	
<b>Xerox® ConnectKey® Apps (Found at the Xerox App Gallery)</b>	Increase user productivity by simplifying and shortening everyday tasks. Unlike traditional software, ConnectKey® Apps do not require a dedicated server, PC or IT resource. Instead, simply download these lightweight, serverless ConnectKey® Apps to the ConnectKey® Technology-enabled multifunction printer.
<b>PSTN ONE-LINE OR THREE-LINE FAX (OPTIONAL)</b>	
<b>FAX<sup>5</sup></b>	
<b>Fax Speed</b>	33.6 Kbps
<b>Resolution</b>	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
<b>Compression</b>	MH, MR, MMR, JBIG
<b>Fax Features</b>	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts)
<b>FAX OVER IP (OPTIONAL)</b>	
<b>Compliance</b>	T.38 compliant IP/SIP
<b>Resolution</b>	Standard 200 x 100 dpi, Fine 200 x 200 dpi, Super Fine 300 x 300, 400 x 400, 600 x 600 dpi
<b>Compression</b>	MH, MR, MMR, JBIG
<b>Fax Features</b>	Walk-up Fax, includes LAN Fax, Direct Fax, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts)
<b>MOBILE SOLUTIONS AND MOBILE DEVICE APPS</b>	
<b>Apple® AirPrint®</b>	Print email, photos and important office documents directly from an Apple iPhone® or iPad® with no drivers to install and no cables to connect. With AirPrint, an iPhone or iPad automatically locates and connects to the AirPrint-enabled device over the office Wi-Fi network.
<b>Mopria® Print Services</b>	ConnectKey® Technology-enabled print devices are Mopria® certified. Mopria® certification ensures you can print wirelessly from your Mopria® supported (Android) smart phone, tablet and other mobile devices instantly and easily.
<b>@PrintByXerox App</b>	@PrintByXerox App is a free service that allows secure printing from any email-enabled device (computer, phone, tablet, iOS, Android™, Google® Chromebook™ and more) to a Xerox® printer or MFP using a single email address with no IT intervention. No training is needed. End-users simply send attachments to the email address, and release them at the MFP panel.
<b>Xerox® Print Service Plug-in for Android™ (Free at Google Play™ Store)</b>	The Xerox® Print Service Plug-in for Android KitKat (4.4 or greater) devices streamlines mobile printing without third-party apps or additional print drivers. You can easily print photos, web pages and documents when your mobile device is connected to multifunction printers using a wireless network. A robust print option set includes two-sided printing, stapling and secure code release. A free download is available from the Google Play™ store.
<b>Xerox® Workplace Mobile App (download from the Xerox App Gallery)</b>	The Xerox® Workplace Mobile App gives you the personal contactless connection you need with your multifunction printer (MFP), allowing you to save time on daily tasks and get work done safely. You can scan, print, copy or release jobs using your mobile smartphone as a remote control, without having to touch your MFP user panel. It takes the guesswork out of quickly and securely connecting your iOS and Android devices to your Xerox® MFP. Download the app for free. Use it with Xerox® Workplace Solutions to access advanced features.
<b>Xerox® Workplace Suite and Xerox® Workplace Cloud</b>	Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.

SECURITY	
<b>Security Features</b>	Access Controls AES 256-bit Encryption Audit Log Certificate Path Validation Certificate Revocation List (CRL)/Status Protocol (OCSP) Detection of External Program Falsification (XCP Plug-in) Cisco® Identity Services Engine (ISE) Integration Domain Filtering FIPS 140-2 Firmware Verification Immediate Disk Overwrite* IP Address Filtering IPsec Network Authentication Port Filtering Pre-installed Self-Signed Certificates Role Based Permissions Secure Email Secure Fax Secure Print Security Certificate Management Smart Card Enablement (CAC/PIV/.NET) SNMPv3 Status Protocol (OCSP) TLS/SSL *Requires HDD/Productivity Kit
ACCOUNTING	
XEROX® STANDARD ACCOUNTING/NETWORK ACCOUNTING (STANDARD)	
<b>Tracking</b>	Copy, Print, Fax, Scan and Email usage
<b>Accounting</b>	Xerox® Standard Accounting Feature Up to 1,000 User Accounts without HDD Up to 9,999 User Accounts with HDD Up to 500 General Accounts Network Accounting (Job Based Accounting) Up to 1,000 User IDs; Up to 1,000 Account IDs without HDD Up to 60,000 User IDs; Up to 60,000 Account IDs with HDD Up to 14,000 Accounting Records (transactions)
<b>Features</b>	Administrator can manage the feature via the Embedded Web Server.
ACCOUNTING OPTIONS – NETWORK ACCOUNTING (ALLOWS CENTRAL SERVER TO MANAGE ALL ACCOUNTING)	
	<ul style="list-style-type: none"> <li>Enhanced network accounting with up to the minute data on how the system is being used</li> <li>Comprehensive management and enterprise scale tracking and reporting of device usage of copy, print, scan and fax</li> <li>Numerous solutions are available through Xerox Alliance Partners. For details visit <a href="http://www.xerox.com">www.xerox.com</a></li> <li>Security enhancements include simultaneous support for HTTP/HTTPS protocols</li> <li>Device requests account authentication from third party server enabling larger databases of users and accounts</li> <li>Accept Authentication Login at control panel and pass to third party Networking Account</li> </ul>

<b>PAPER HANDLING</b>	
<b>DOCUMENT FEEDER</b>	
<b>Capacity<sup>6</sup></b>	Duplex Automatic Document Feeder (DADF): 110 sheets
<b>Sizes</b> One-sided: Two-sided:	Custom sizes: 4.92 x 3.35 in. to 11.69 x 17 in./125 x 85 mm to 297 x 431.8 mm 4.92 x 4.33 in. to 11.69 x 17 in./125 x 110 mm to 297 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	11 to 34 lb. bond/38 to 128 gsm 13 to 34 lb. bond/50 to 128 gsm
<b>BYPASS TRAY</b>	
<b>Capacity<sup>6</sup></b>	100 sheets
<b>Sizes</b>	Custom sizes: 3.5 x 3.87 in. to 11.69 x 17 in./88.9 x 98.4 mm to 297 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 80 lb. cover/60 to 216 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
<b>Types</b>	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Pre-Printed Recycled
<b>TRAY 1</b>	
<b>Capacity<sup>6</sup></b>	520 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
<b>Types</b>	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled



<b>SINGLE TRAY MODULE (OPTIONAL – BASE MODEL ONLY)</b>	
<b>Capacity<sup>6</sup></b>	520 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
<b>Types</b>	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
<b>SINGLE TRAY MODULE WITH STAND (OPTIONAL)</b>	
<b>Capacity<sup>6</sup></b>	520 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
<b>Types</b>	Bond Plain Paper Cardstock Custom Envelopes Hole Punched Labels Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Pre-Printed Recycled
<b>THREE TRAY MODULE (OPTIONAL)</b>	
<b>Capacity<sup>6</sup></b>	Tray 2: 520 sheets Tray 3: 520 sheets Tray 4: 520 sheets
<b>Sizes</b>	Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm

<b>Types</b>	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
<b>HIGH CAPACITY TANDEM TRAY MODULE (OPTIONAL)</b>	
<b>Capacity<sup>6</sup></b>	Tray 2: 520 sheets Tray 3: 870 sheets Tray 4: 1,130 sheets
<b>Sizes</b>	Tray 2: Custom sizes: 5.5 x 7.17 in. to 11.69 x 17 in./139.7 x 182.0 mm to 297.0 x 431.8 mm Tray 3: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5 Tray 4: Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5
<b>Weights</b> One-sided: Two-sided:	16 lb. bond to 95 lb. cover/60 to 256 gsm 16 lb. bond to 60 lb. cover/60 to 169 gsm
<b>Types</b>	Bond Plain Paper Cardstock Custom Hole Punched Labels Heavyweight Labels Extra Heavyweight Labels Letterhead Lightweight Cardstock Lightweight Glossy Cardstock Lightweight Glossy Cardstock Reload Heavyweight Cardstock Pre-Printed Recycled
<b>ENVELOPE TRAY – REPLACES TRAY 1 (OPTIONAL)</b>	
<b>Capacity<sup>6</sup></b>	Up to 60 envelopes
<b>Sizes</b>	#10 commercial, Monarch, DL, C5 Custom sizes: 3.9 x 5.8 in. to 6.4 x 9.5 in./98 x 148 mm to 162 x 241 mm
<b>Weights</b>	20 to 25 lb. bond/75 to 90 gsm
<b>HIGH CAPACITY FEEDER (OPTIONAL)</b>	
<b>Capacity<sup>6</sup></b>	2,000 sheets
<b>Sizes</b>	Standard Sizes: 8.5 x 11 in. and 7.25 x 10.5 in./A4 or B5

<b>Weights</b>	
One-sided:	16 lb. bond to 80 lb. cover/60 to 216 gsm
Two-sided:	16 lb. bond to 60 lb. cover/60 to 169 gsm
<b>TOTAL CAPACITY</b>	
<b>Base Unit Capacity<sup>6</sup></b>	620 sheets
<b>Single Tray Module Capacity<sup>6</sup></b>	1,140 sheets
<b>Single Tray Module with Stand Capacity<sup>6</sup></b>	1,140 sheets
<b>Three Tray Module Capacity<sup>6</sup></b>	2,180 sheets
<b>High-Capacity Tandem Tray Capacity<sup>6</sup></b>	3,140 sheets
<b>FINISHING</b>	
<b>OUTPUT TRAYS (OPTIONAL ON BASE MODEL)</b>	
<b>Dual Catch Trays<sup>6</sup></b>	250 sheets each; Lower tray offsets
<b>INTEGRATED OFFICE FINISHER TYPE A AND INTEGRATED OFFICE FINISHER (OPTIONAL)</b>	
<b>Stacking Tray</b>	500 sheets of 20 lb. bond/80 gsm – 8.5 x 11 in./A4 or 250 sheets of 20 lb. bond/80 gsm – 11 x 17 in./A3
<b>Sizes</b>	3.5 x 3.9 in. to 11.7 x 17 in./89 x 98 mm to 297 x 432 mm
<b>Weights</b>	Integrated Office Finisher Type A: 16 lb. bond to 80 lb. cover/60 to 220 gsm Integrated Office Finisher: 16 lb. bond to 95 lb. cover/60 to 256 gsm
<b>Stapling</b>	Dual Auto Stapling (Single for Type A): 50 sheets maximum: Letter/A4/B5-size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal/Tabloid/A3/B4-size sheets (less than 90 gsm or (2) 220 gsm covers)
<b>OFFICE FINISHERS (OPTIONAL)</b>	
<b>Capacity<sup>6</sup></b>	Stacking Tray: 2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (8.5 x 11 in./A4) (dual stapling only with optional booklet maker)
<b>Sizes:</b> <b>Office Finisher LX</b> <b>Office Finisher</b>	8.3 x 7.2 in. to 11.7 x 17 in./210 x 182 mm to 297 x 432 mm 5.8 x 11.7 in. to 5.8 x 17 in./148.0 x 297.0 mm to 148.0 to 432.0 mm
<b>Weights</b>	Office Finisher LX: 16 lb. bond to 80 lb. cover/60 to 220 gsm Office Finisher: 16 lb. bond to 80 lb. cover/60 to 256 gsm
<b>Multiposition Stapling</b>	50 sheets of 24 lb. bond/90 gsm
<b>Hole Punch (Optional)</b> <b>North America:</b> <b>Europe:</b>	Office Finisher LX up to 65 lb. cover (200 gsm)/Office Finisher up to 80 lb. cover (220 gsm) 2-3 Hole Punch 2-4 Hole Punch
<b>BOOKLET MAKER FOR OFFICE FINISHERS (SCORE/CREASE, SADDLE-STITCH STAPLE) (OPTIONAL)</b>	
<b>Capacity<sup>6</sup></b>	40 booklets (2-15 sheets per booklet – 20 lb./80 gsm or less)
<b>Sizes</b>	Letter – 8.5 x 11 in./A4 SEF Legal – 8.5 x 14 in./B4 SEF Ledger – 11 x 17 in./A3 SEF
<b>Saddle-stitch Stapling</b>	2-15 sheets/8-60 page booklet Office Finisher LX: 16 lb. bond to 24 lb. bond/60 to 90 gsm Office Finisher: 16 lb. bond to 80 lb. cover/64 to 220 gsm
<b>Score/Crease</b>	1-15 sheets/unstapled/64 -105 gsm
<b>CONVENIENCE STAPLER AND WORK SURFACE (OPTIONAL)</b>	
<b>Capacity<sup>6</sup></b>	50-sheet stapling 5,000 staples Requires a separate outlet

<b>DEVICE MANAGEMENT</b>	
<b>Network Protocols</b>	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD LDAP Bonjour®/AirPrint™ FTP Most protocols not in use can be disabled
<b>Administrative Protocols</b>	DHCP, SNMP, WINS, HTTP, HTTPS, TLS, SNTP, MDNS
<b>XEROX® CENTREWARE® WEB SOFTWARE</b>	
	<ul style="list-style-type: none"> <li>• A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows or UNIX or any other operating system</li> <li>• Works with any SNMP-managed printer from any manufacturer</li> <li>• Provides help with device discovery and installations, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management</li> </ul>
<b>EMBEDDED WEB SERVER – INTEGRATED DEVICE WEB PAGE</b>	
<b>Device Status</b>	<ul style="list-style-type: none"> <li>• Tray Status/Contents</li> <li>• Consumables Status</li> <li>• Billing/Usage</li> <li>• Quick Links</li> <li>• Online Support</li> </ul>
<b>Print Queue Viewing</b>	Job print queue management — view and delete
<b>Job Submission</b>	Print-ready files (PS (with optional PostScript option), PCL, PDF, XPS, JPEG)
<b>Device Administration</b>	Allows simple, remote installation setting of configuration options and management of the device
<b>Browsers</b>	Microsoft® Internet Explorer® Microsoft Edge™ Mozilla™ Firefox® Apple® Safari® Google Chrome™
<b>REMOTE SERVICES</b>	
<b>Xerox® Automatic Meter Readings (AMR)</b>	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
<b>Automatic Supplies Replenishment (ASR)</b>	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.

SUPPLIES AND ACCESSORIES	QUANTITY	PART NUMBER
<b>SUPPLIES</b>		
<b>High Capacity Print Cartridges<sup>7</sup></b>	Cyan: 9,800 standard pages Magenta: 9,800 standard pages Yellow: 9,800 standard pages Black: 16,100 standard pages	106R03744 106R03743 106R03742 106R03741
<b>Extra High Capacity Print Cartridges<sup>7</sup></b>	Cyan: 16,500 standard pages Magenta: 16,500 standard pages Yellow: 16,500 standard pages Black: 23,600 standard pages	106R03740 106R03739 106R03738 106R03737
<b>Metered Print Cartridges<sup>8</sup></b>	Cyan: 15,000 standard pages Magenta: 15,000 standard pages Yellow: 15,000 standard pages Black: 22,000 standard pages	106R03736 106R03735 106R03734 106R03733
<b>Drum Cartridge<sup>9</sup></b>	Black: 109,000 Cyan, Magenta, Yellow: 87,000 standard pages	113R00780
<b>Waste Toner Bottle</b>	30,000	115R00128
<b>Office Finishers Booklet Maker Cartridge (8 cartridges per container)</b>	16,000 staples (2,000 each cartridge)	008R12897
<b>Staple Refills for Finishers (3 refills per container)</b>	15,000 staples (5,000 each refill)	008R12941
<b>Staple Cartridge for Finishers (1 cartridge per container)</b>	5,000 staples (5,000 each cartridge)	008R12964

# Xerox® VersaLink® C7020/C7025/C7030 Color Multifunction Printer

ACCESSORIES/OPTIONS	PART NUMBER
Single Tray Module (does not include Stand – for Desktop Model only)	097S04910
Single Tray with Stand Module	097S04907
Three Tray Module	097S04908
High Capacity Tandem Tray Module	097S04909
Envelope Tray (Replaces Tray 1)	497K17720
Center Output Tray (Dual Catch Tray) (Optional on Desktop Model)	497K17800
HDD (320 GB hard drive) (Optional on Desktop Model)	497K17740
Integrated Office Finisher (Type A)	097S04911
Integrated Office Finisher	097S04847
Office Finisher LX	097S04848
Office Finisher	097S05019
Booklet Maker for Office Finisher LX	497K03852
Booklet Maker for Office Finisher	497K20590
2/3 Hole Punch for Office Finisher LX (available in Western Hemisphere)	497K03860
2/3 Hole Punch for Office Finisher (available in Western Hemisphere)	497K20600
2/4 Hole Punch for Office Finisher LX (available in Eastern Hemisphere)	497K03870
2/4 Hole Punch for Office Finisher (available in Eastern Hemisphere)	497K20610
1 Line Fax Kit (PSTN Fax)	497K17750
3 Line Fax Kit (PSTN Fax)	497K17760
Wireless Network Adapter Kit	497K16750
Internal Card Reader/RFID Kit	497K18120
PostScript Kit	497K18340
Fax Over IP Kit	497K18330

<sup>1</sup> Declared print speed in accordance with ISO/IEC 24734.

<sup>2</sup> Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

<sup>3</sup> Expected regular monthly throughput.

<sup>4</sup> Power states defined per ENERGY STAR® Program requirements for Imaging Equipment.

<sup>5</sup> Requires analog phone line.

<sup>6</sup> Paper capacities are based on 20 lb./75 gsm stock; capacities will vary with different weight stocks.

<sup>7</sup> Average standard pages. Declared Yield in accordance with ISO/IEC 19798. Yield will vary based on image, area coverage and print mode.

<sup>8</sup> Assumptions: Toner cartridge yield is based on 5% area coverage on 8.5 x 11 in./A4 LEF. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, run mode, application types, monthly print volumes and image quality set-points.

<sup>9</sup> Approximate pages. Declared yield will vary depending on job run length, media size/orientation and machine speed.

For more information visit: <https://www.office.xerox.com/Latest/SUPGL-01.pdf>.

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program.

For more information, visit [www.xerox.com/About-Xerox/Recycling](http://www.xerox.com/About-Xerox/Recycling).

For more information, visit us at [www.xerox.com/Office](http://www.xerox.com/Office).

Configurations vary by geography.